

KMB4

"KMB4" BOX WITH PASSIVE SAFETY ZENER BARRIERS, FOR ATEX ENVIRONMENTS



Kit of three intrinsic protection Zener barriers, for connection of devices in ATEX area with devices in safe area, housed in an ABS box.

Marking of single barrier: ATEX II (1) GD [Ex ia Ga] IIC [Ex ia Da] IIIC.

Marking of the whole box with three Zener

SINGLE CHANNEL FEATURES

• Barrier for signal and sense:

Fuse: 50mA
Uo: 8.7V
Io: 25mA
Po: 0,05W
Co: 5,9μF
Lo: 56,88mH
8 Ω
8 3 6

• Barrier for supply:

Fuse: 100mA Uo: 12V Io: 164mA Po: 0,49W Co: 1,41 μ F Lo: 1,32mH 85 Ω 85 3

• NOTE: connection with up to 4 load cells of 350 ohm each.




WARNING

The KMB4 kit can be placed in ATEX zone according to its ATEX marking or in alternative in a safe area.



The electric coordination, executed for realizing the DCATEXMB4 certificate, involves the use of the LCCB cable, maximum length of 50m (greater lengths upon price estimate).








KMB4: dimensions in mm.

3 zener barriers for load cell supply, signal, and sense. Suitable for mounting on a DIN bar in a safe area, or in a hazardous-proof case (Exd) in an ATEX area.





DINI ARGEO FRANCE sarl Nogent-sur-Marne DINI ARGEO **GMBH**

Sinsheim - Germany

DINI ARGEO UK Ltd

Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd

Shanghai - China

DINI ARGEO WEIGHBRIDGES Calto (RO) - Italy



HEAD OFFICE Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy







VAHY PRO S.R.O.

FUGNEROVA 345 - 40004 - TRMICE

Tel. 0042-0475620800 Fax. 0042-0475620800

vahypro@vahypro.cz

 $SALES\ AND\ TECHNICAL\ ASSISTANCE\ SERVICE$