

JBQAI

"JBQAI": EQUALISED JUNCTION BOX FOR ATEX ENVIRONMENTS



Stainless steel junction box with IP66 protection from water and dust, and fitted with an intrinsically safe electronic board for junction and equalisation of load cells. Terminal boards with screws for easing th connection of the load cells and signal adjustment trimmer, for an accurate and reliable equalisation.

Marking:

ATEX II 2G Ex ib IIC T6 Gb for gases.

ATEX II 2D Ex tb IIIC T115°C Db IP65 for dust.

TECHNICAL FEATURES

- Designed and made according to the ATEX 94/9/CE directive, group II category 2GD, according to the IEC/EN60079-0, IEC/EN60079-11, and IEC/EN60079-31 norms.
- Stainless steel case.
- Protection degree: IP66.
- Dimensions: 190x130x45mm (lxwxh).

NOTE: the dimensions are not compatibles for mounting on 4 load cells platforms/pallet weighers.

ATEX PARAMETERS OF THE JUNCTION BOX

- Uo = Ui = 24Vdc
- Io = Ii = 174mA
- Co = Ci = 0mF
- Lo = Li = 0mH

or

- Uo = Ui = 12Vdc
- Io = Ii = 3,33A
- Co = Ci = 0mF
- Lo = Li = 0mH





DINI ARGEO FRANCE sarl Nogent-sur-Marne

DINI ARGEO **GMBH** Sinsheim - Germany

UK Ltd

Taunton - United Kingdom

DINI ARGEO

DINI ARGEO WEIGHING INSTRUMENTS Ltd Shanghai - China

DINI ARGEO WEIGHBRIDGES Calto (RO) - Italy



HEAD OFFICE Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy







VAHY PRO S.R.O.

FUGNEROVA 345 - 40004 - TRMICE

Tel. 0042-0475620800 Fax. 0042-0475620800

vahypro@vahypro.cz

 $SALES\ AND\ TECHNICAL\ ASSISTANCE\ SERVICE$